

# VTO3211D-P2

## IP 2-button Villa Outdoor Station



### Features

- 2MP HD CMOS camera
- Aluminum panel, IP65,IK08
- ICR Night vision &Voice indication
- Video & Audio messaging
- Remote intercom with mobile APP
- Surface mounted



### Technical Specification

Model	VTO3211D-P2
-------	-------------

#### System

Main Processor	Embedded Micro Processor
Operation System	Embedded LINUX OS

#### Video

Video Compression	H.264
Image Sensor	1/2.8" 2MP CMOS
Focal Length	1.9mm
Angle of View	H:140°
Day/Night	ICR

#### Audio

Audio Compression	G.711
Audio Input	Omnidirectional Mic
Audio Output	Built-in Speaker
Bidirectional Talk	Support Dual-way Bidirectional talk

#### Operation Mode

Keypad	1/2/4 Mechanical Buttons
Reader	Mifare Card

#### Interface

Door Control	1
Alarm In	2(1ch unlock button, 1ch feedback)
RS485	1

#### Network

Ethernet	10M/100Mbps Self-adaptive
Network Protocol	TCP/IP


Ethernet	10M/100Mbps Self-adaptive
----------	---------------------------

Network Protocol	TCP/IP
------------------	--------


#### General

Ingress Protection	IP65, IK08
Tamper Switch	1
Installation	Surface
Material	Aluminum
Power	DC 12V, PoE(802.3af)
Power Consumption	Standby ≤1W, Work ≤7W
Working Temperature	-40°C~+60°C
Relative Humidity	10%~90%RH
Dimensions	182.0mm×30.0mm×101.0mm
Weight	0.8Kg

Dimensions



View Area



Application

