

Cambium PTP-LPU Hazardous Location Guide



Cambium Networks™

Accuracy

While reasonable efforts have been made to assure the accuracy of this document, Cambium Networks assumes no liability resulting from any inaccuracies or omissions in this document, or from use of the information obtained herein. Cambium Networks reserves the right to make changes to any products described herein to improve reliability, function, or design, and reserves the right to revise this document and to make changes from time to time in content hereof with no obligation to notify any person of revisions or changes. Cambium Networks does not assume any liability arising out of the application or use of any product, software, or circuit described herein; neither does it convey license under its patent rights or the rights of others. It is possible that this publication may contain references to, or information about Cambium Networks products (machines and programs), programming, or services that are not announced in your country. Such references or information must not be construed to mean that Cambium Networks intends to announce such Cambium Networks products, programming, or services in your country.

Copyrights

This document, Cambium Networks products, and 3rd Party software products described in this document may include or describe copyrighted Cambium Networks and other 3rd Party supplied computer programs stored in semiconductor memories or other media. Laws in the United States and other countries preserve for Cambium Networks, its licensors, and other 3rd Party supplied software certain exclusive rights for copyrighted material, including the exclusive right to copy, reproduce in any form, distribute and make derivative works of the copyrighted material. Accordingly, any copyrighted material of Cambium Networks, its licensors, or the 3rd Party software supplied material contained in the Cambium Networks products described in this document may not be copied, reproduced, reverse engineered, distributed, merged or modified in any manner without the express written permission of Cambium Networks. Furthermore, the purchase of Cambium Networks products shall not be deemed to grant either directly or by implication, estoppel, or otherwise, any license under the copyrights, patents or patent applications of Cambium Networks or other 3rd Party supplied software, except for the normal non-exclusive, royalty free license to use that arises by operation of law in the sale of a product.

Restrictions

Software and documentation are copyrighted materials. Making unauthorized copies is prohibited by law. No part of the software or documentation may be reproduced, transmitted, transcribed, stored in a retrieval system, or translated into any language or computer language, in any form or by any means, without prior written permission of Cambium Networks.

License Agreements

The software described in this document is the property of Cambium Networks and its licensors. It is furnished by express license agreement only and may be used only in accordance with the terms of such an agreement.

High Risk Materials

Cambium and its supplier(s) specifically disclaim any express or implied warranty of fitness for any high risk activities or uses of its products including, but not limited to, the operation of nuclear facilities, aircraft navigation or aircraft communication systems, air traffic control, life support, or weapons systems (“High Risk Use”). Any High Risk is unauthorized, is made at your own risk and you shall be responsible for any and all losses, damage or claims arising out of any High Risk Use.

About this guide

This guide identifies the specific requirements that must be met by the installer and operator of the Cambium Networks PTP-LPU when the product is intended for use in Hazardous Locations.

Hazardous Locations are those covered by the ATEX regulations in Europe and the HAZLOC regulations in the USA.

Version information

Document number and version: phn-4432 002v000 (March 2017).

User documentation

For full PTP-LPU installation planning instructions and a list of components, download phn-3348 - PTP 650 LPU and Grounding Kit Installation Guide from:

<https://support.cambiumnetworks.com/files/ptp650/>

Important safety information



Warning

To prevent fire and explosions when installing or operating the PTP-LPU in hazardous locations, observe the instructions in this guide.

Checking labels

Only products marked with the qualification label shown in [Product labels](#) on page 6 may be used in hazardous locations.

Special conditions

PTP-LPU specific:

- 1) Connection and disconnection of terminals and plugs when the equipment is energised is strictly prohibited.
- 2) Only ATEX certified AC + DC Enhanced Power Injector models (EMT16ATEX0052X / IECEx EMT 16.0029X) provided by Cambium Networks Ltd may be used in conjunction with the equipment.
- 3) The connections into the hazardous areas from the AC + DC Enhanced Power Injector (EMT16ATEX0052X/ IECEx EMT 16.0029X) to the LPU are at incendive energy levels and so they shall be made using protective shielded cable that provides protection from impact and damage in accordance with EN/IEC 60079-14.

Allowed operating envelope

The PTP-LPU has been certified for operation in the following hazardous locations:

ATEX

The products have been approved under an 'Intrinsic Safety' assessment as defined in EN/IEC 60079-11:2012.

Approval is given by IECEX certificate number IECEX EMT 16.0028X and ATEX certificate number EMT16ATEX0051X, issued by Element Materials Limited, with the specific level of coverage shown below.

- II 3 G Ex ic IIC T4 Gc
- II - Equipment group (surface applications)
- 3 - Equipment category (infrequent exposure)
- G - Atmosphere (Gas)
- ic - Protection concept (intrinsic safety)
- IIC - Gas group (up to and including Hydrogen and Acetylene)
- T4 - Temperature class (135°C)
- Gc - Equipment Protection Level

HAZLOC

The products have been assessed and found compliant with the requirements of ANSI 12.12.01 and CSA C22.2 No. 213 for the following conditions.

The approval is given by MET Labs under File Reference E113068, with the specific level of coverage shown below.

- Complies with ANSI 12.12.01 and CSA C22.2 No. 213
- Class I - Gases, Vapors and Liquids (surface applications)
- Div - 2 (Infrequent Exposure)
- Gas Groups - A, B, C, D (up to and including Hydrogen and Acetylene)
- Operating Temperature Code - T4 (135°C)

Part numbers and product labels

Part numbers


The PTP-LPU is supplied as a kit under the part number shown in [Table 1](#) below.

Table 1 PTP- LPU model/part number

| LPU model / part number | Description |
|----------------------------|---|
| C000065L007B | PTP-LPU and Grounding Kit (1 kit per END) |

Product labels

Figure 1 Certification label on PTP-LPU



Installation and operating requirements

Environmental requirements

The PTP-LPU complies with the reduced circuit separation requirements of EN/IEC 60079-11:2012 Annex F. The product is protected by enclosures rated to IP67.

Dielectric strength

The PTP-LPU is a surge suppression device designed to shunt abnormal voltage surges to ground. The intrinsically-safe-circuit-to-ground dielectric strength is nominally 90 V dc.

General requirements

ATEX regulatory environments

Installation should be in accordance with the requirements of EN/IEC 60079-14 as applicable.

HAZLOC regulatory environments

Installation should be in accordance with the National Electrical Code (NEC) and relevant OSHA standard.

Warnings

Before installing these products, read [Important safety information](#) on page 4.

Contact us

| | |
|------------------------|---|
| Support website: | http://www.cambiumnetworks.com/support |
| Main website: | http://www.cambiumnetworks.com |
| Sales enquiries: | solutions@cambiumnetworks.com |
| Support enquiries: | support@cambiumnetworks.com |
| Repair enquiries | rma@cambiumnetworks.com |
| Telephone number list: | http://www.cambiumnetworks.com/support/contact-support |
| Address: | Cambium Networks Inc. 3800 Golf Road, Suite 360 Rolling Meadows IL 60008 USA |