

UTP3-SW08-TP120-A1




- Main ports: 8 downlink Fast PoE Ethernet ports, 2 Ethernet ports Gigabit uplink
- Special Function One Key CCTV Mode: Support VLAN and restrict the storm of grid; 1~8 downlink ports can only communicate with uplink ports; the additional transmission distance up to 250m in mode CCTV with a transmission speed of 10 Mbps;
- Standard: IEEE802.3, IEEE802.3u, IEEE802.3af, IEEE802.3at;
- Protection: superior lightning protection (6KV), ESD protection and anti-interference ability;
- Structure: stable and delicate, easy to install; Operation: plug and play, no configuration is needed.




Introduction

The 8-port switch with 8 downlink PoE ports and dual 1000Mbps uplink ports is a security surveillance POE switch that is applied in high definition network surveillance and security systems. The product fully combines the features of security surveillance. In addition, the 8 PoE ports Downlink devices support the IEEE802.3af/at standard. ESD, 6KV surge and lightning protection circuits enhance product stability. Also, the device supports one key CCTV mode which realizes VLAN function, restricts network storm, protects information security, prevents virus spreading and cyber attack, fully satisfy the Ethernet video security surveillance system and the needs of Ethernet projects.


Applications



physical characteristics



interface drawing



Specification

Model	UTP3-SW08-TP120-A1
downlink ports	8 10 / 100Base-TX (PoE)
uplink ports	2 10/100 / 1000Base-T
network standard	IEEE802.3, IEEE802.3u, IEEE802.3ab
change fabric	5,6 Gbps
Performance	4.2Mpps @ 64Bytes
Switch Arquitectura	store and forward
Shared data buffer	1.5 million
MAC address table	4K
PoE standard	IEEE 802.3af / at (PSE)
PSE type	final stretch
Power Pin Assignment	1/2 (+) y 3/6 (-)
PoE power output	48 ~ 57 V DC, single port 30 watts max.
PoE Budge	120 watts maximum
lightning protection	6KV Execute: IEC61000-4-5
ESD	6KV contact download 8KV air discharge Execute: IEC61000-4-2
Power supply	CC 48 V ~ 57 V
power dissipation	y 5W
Work temperature	- 10 y - 55 y
Storage temperature	- 40 y - 85 y
Humidity (non-condensing)	5% -95%
DimensionyLxWxHy	200 mm x 101,8 mm x 27 mm
Weight	500g
Regulator	THIS , FCC , ROHS

package list

Designation	Quantity
UTP3-SW08-TP120-A1	1
Power adapter	1
Accessory	1
User's manual	1

related products

Designation	Model
4 Port Fast PoE Switch	UTP3-SW04-TP60
8-port fast PoE	UTP3-SW08-TP120